

Optional extras for piston valves

Outlet Nozzles



Part No Straight Short Outlet Nozzle
A267 with 20 mm bore
 Manufactured in 316 st.steel



Part No Straight Long Outlet Nozzle
A269 with 20 mm bore

A268 with 25 mm bore
 Manufactured in 316 st.steel

Bottle Outlets



Part No Straight standard vented bottle Outlet
A257 with GL 45 Cap. 20 mm bore to 10 mm pipe

A258 with cap to suit 8 oz bottle. 20 mm bore to 10 mm pipe
 Manufactured in 316 st.steel



Part No Angled Vented Bottle Outlet
A259 With GL 45 cap. 20 mm bore
 Manufactured in 316 st.steel

Flanged outlet



Part No Flanged outlet
A260 For connection to 1" NB pipeline class 150
 Manufactured in 316 st.steel

Optional extras for piston valves

Outlet screwed caps



Part No

DP4-2067

316L stainless steel cap to fit GL45 bottle outlet complete with chain to attach to valve

Firesafe Secondary Ball Valve



Part No

F44

secondary Firesafe Ball Valve, 20mm nominal bore manufactured in 316L stainless steel, to provide quick shut off between the outlet flange of the valve and the various straight, long and angled outlets

FOSBA GmbH

Itzelstein 15
59929 Brilon -Germany

Tel.: +49 2961 9119233
Fax: +49 2961 9119250

e-mail: info@fosba.de
web: www.fosba.de